

# IServ an Nextcloud anbinden (LDAP)

Zunächst muss man auf dem IServ den LDAP-Zugriff [vorbereiten](#). Das mitgelieferte Plugin von Nextcloud schreibt leider ungeeignete Daten in die Nextcloud-Datenbank, so dass man z.B. mit phpmyadmin manuell Werte in die Datenbank schreiben muss.

Die relevanten Einträge befinden sich in der Tabelle `oc_appconfig` und besitzen in der Spalte `appid` den Eintrag `user_ldap`.

cleanUpJobOffset	100	
enabled	yes	
installed version	1.8.0	
lastChange	1606087775	
ldap_memberof_filter_support	1	
home_folder_naming_rule		
last_jpegPhoto_lookup	0	
ldap_ajgm_password	MEERSTEINSCHERESPASSWORT	
ldap_attributes_for_group_search		
ldap_attributes_for_user_search		
ldap_backup_host		
ldap_backup_port		
ldap_base	dc=schule,dc=ts	
ldap_base_groups	dc=schule,dc=ts	
ldap_base_users		
ldap_cache_ttl	600	
ldap_combination_active	1	
ldap_default_policy_dn		
ldap_display_name	gecos	
ldap_dn	nextcloud.ou=ldap,dc=schule,dc=ts	
ldap_dynamic_group_member_uf		
ldap_email_attr	mail	
ldap_experienced_admin	0	
ldap_expert_username_attr		
ldap_expert_uid_group_attr		
ldap_expert_uid_user_attr		
ldap_ext_storage_home_attribute		
ldap_gid_number	gidNumber	
ldap_group_display_name	cn	
ldap_group_filter	&( (objectclass=posixGroup)(cn=GRUPPE)(cn=GRUPPE)(cn=GRUPPE))	
ldap_group_filter_mode	1	
ldap_group_member_assoc_attribute	memberof	
ldap_groupfilter_groups	GRUPPE	
ldap_groupfilter_objectclass	posixGroup	
ldap_host	ldap://schule.ts	
ldap_login_filter	&(	memberof=cn=GRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(memberof=cn=NOCH-KEINEGRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(memberof=cn=WETTERGRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(uid=*)
ldap_login_filter_mode	1	
ldap_loginfilter_attributes		
ldap_loginfilter_email	0	
ldap_loginfilter_username	1	
ldap_nested_groups	0	
ldap_override_main_server	1	
ldap_page_size	500	
ldap_port	10636	
ldap_quota_attr		
ldap_quota_def		
ldap_tls	0	
ldap_turn_off_cert_check	0	
ldap_turn_on_pwd_change	0	
ldap_user_availability	default	
ldap_user_display_name_2		
ldap_user_filter_mode	1	
ldap_userfilter_groups	GRUPPE	
ldap_userfilter_objectclass		
ldap_userfilter_filter	(memberof=cn=GRUPPE,ou=groups,dc=schule,dc=ts)(memberof=cn=GRUPPE,ou=groups,dc=schule,dc=ts)(memberof=cn=GRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)	
ldap_userfilter_to_object_memberof_2		
ldap_authentication	authentication	

From: <https://wiki.mzclp.de/> - Fortbildungswiki des Medienzentrums Cloppenburg

Permanent link: <https://wiki.mzclp.de/doku.php?id=anleitung:iservnextcloudldap&rev=1623915124>

Last update: 2021/06/17 09:32

