

IServ an Nextcloud anbinden (LDAP)

Zunächst muss man auf dem IServ den LDAP-Zugriff [vorbereiten](#). Das mitgelieferte Plugin von Nextcloud schreibt leider ungeeignete Daten in die Nextcloud-Datenbank, so dass man z.B. mit phpmyadmin manuell Werte in die Datenbank schreiben muss.

Die relevanten Einträge befinden sich in der Tabelle `oc_appconfig` und besitzen in der Spalte `appid` den Eintrag `user_ldap`.

Datenbankfeld	Wert	Kommentar
cleanUpJobOffset	100	
enabled	yes	
installed_version	1.8.0	
s01_lastChange	1606067775	
s01has memberof filter support	1	
s01home folder naming rule		
s01last jpegPhoto lookup	0	
s01ldap_agent_password	HIERSTEHTEINSICHERESPASSWORT	
s01ldap_attributes_for_group_search		
s01ldap_attributes_for_user_search		
s01ldap_backup_host		
s01ldap_backup_port		
s01ldap_base	dc=schule,dc=tld	
s01ldap_base_groups	dc=schule,dc=tld	
s01ldap_base_users		
s01ldap_cache_ttl	600	
s01ldap_configuration_active	1	
s01ldap_default_ppolicy_dn		
s01ldap_display_name	gecos	
s01ldap_dn	cn=nextcloud,ou=ldap,dc=schule,dc=tld	
s01ldap_dynamic_group_member_uri		
s01ldap_email_attr	mail	
s01ldap_experienced_admin	0	
s01ldap_expert_username_attr		
s01ldap_expert_uid_group_attr		
s01ldap_expert_uid_user_attr		
s01ldap_ext_storage_home_attribute		
s01ldap_gid_number	gidNumber	
s01ldap_group_display_name	cn	
s01ldap_group_filter	(&((objectclass=posixGroup))((cn=GRUPPE)(cn=GRUPPE)(cn=GRUPPE)(cn=GRUPPE)))	
s01ldap_group_filter_mode	1	
s01ldap_group_member_assoc_attribute	memberUid	
s01ldap_groupfilter_groups	GRUPPE	
s01ldap_groupfilter_objectclass	posixGroup	
s01ldap_host	ldaps://schule.tld	
s01ldap_login_filter	(&((memberof=cn=GRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(memberof=cn=NOCHKEINEGRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(memberof=cn=WEITEREGRUPPE,ou=groups,dc=MEIN-ISERV,dc=de))(uid=%uid))	
s01ldap_login_filter_mode	1	
s01ldap_loginfilter_attributes		
s01ldap_loginfilter_email	0	
s01ldap_loginfilter_username	1	
s01ldap_nested_groups	0	
s01ldap_override_main_server		
s01ldap_paging_size	500	
s01ldap_port	10636	
s01ldap_quota_attr		
s01ldap_quota_def		
s01ldap_tis	0	
s01ldap_turn_off_cert_check	0	
s01ldap_turn_on_pwd_change	0	
s01ldap_user_avatar_rule	default	
s01ldap_user_display_name_2		
s01ldap_user_filter_mode	1	
s01ldap_userfilter_groups	GRUPPE	
s01ldap_userfilter_objectclass		
s01ldap_userlist_filter	((memberof=cn=GRUPPE,ou=groups,dc=schule,dc=tld)(memberof=cn=GRUPPE,ou=groups,dc=schule,dc=tld)(memberof=cn=GRUPPE,ou=groups,dc=MEIN-ISERV,dc=de))	
s01use_memberof_to_detect_membership	1	
types	authentication	

From: <https://wiki.mzclp.de/> - Fortbildungswiki des Medienzentrums Cloppenburg

Permanent link: <https://wiki.mzclp.de/doku.php?id=anleitung:iservnextcloudldap&rev=1623915512>

Last update: 2021/06/17 09:38

