

IServ an Nextcloud anbinden (LDAP)

Zunächst muss man auf dem IServ den LDAP-Zugriff [vorbereiten](#). Das mitgelieferte Plugin von Nextcloud schreibt leider ungeeignete Daten in die Nextcloud-Datenbank, so dass man z.B. mit phpmyadmin manuell Werte in die Datenbank schreiben muss.

Die relevanten Einträge befinden sich in der Tabelle `oc_appconfig` und besitzen in der Spalte `appid` den Eintrag `user_ldap`.

@#F61303:Datenbankfeld	@#F61303:Wert
cleanUpJobOffset	100
enabled	yes
installed_version	1.8.0
s01_lastChange	1606067775
s01has_memberof_filter_support	1
s01home_folder_naming_rule	
s01last_jpegPhoto_lookup	0
s01ldap_agent_password	HIERSTEHEINSICHERESPASSWORT
s01ldap_attributes_for_group_search	
s01ldap_attributes_for_user_search	
s01ldap_backup_host	
s01ldap_backup_port	
s01ldap_base	dc=schule,dc=tld
s01ldap_base_groups	dc=schule,dc=tld
s01ldap_base_users	
s01ldap_cache_ttl	600
s01ldap_configuration_active	1
s01ldap_default_ppolicy_dn	
s01ldap_display_name	gecos
s01ldap_dn	cn=nextcloud,ou=ldap,dc=schule,dc=tld
s01ldap_dynamic_group_member_url	
s01ldap_email_attr	mail
s01ldap_experienced_admin	0
s01ldap_expert_username_attr	
s01ldap_expert_uid_group_attr	
s01ldap_expert_uid_user_attr	
s01ldap_ext_storage_home_attribute	
s01ldap_gid_number	gidNumber
s01ldap_group_display_name	cn
s01ldap_group_filter	(&((objectclass=posixGroup))((cn=GRUPPE)(cn=GRUPPE)(cn=GRUPPE)(cn=GRUPPE)))
s01ldap_group_filter_mode	1
s01ldap_group_member_assoc_attribute	memberUid
s01ldap_groupfilter_groups	GRUPPE
s01ldap_groupfilter_objectclass	posixGroup
s01ldap_host	ldaps://schule.tld
s01ldap_login_filter	(&((memberof=cn=GRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(memberof=cn=NOCHEINEGRUPPE,ou=groups,dc=MEIN-ISERV,dc=de)(memberof=cn=WEITEREGRUPPE,ou=groups,dc=MEIN-ISERV,dc=de))(uid=%uid))
s01ldap_login_filter_mode	1
s01ldap_loginfilter_attributes	
s01ldap_loginfilter_email	0
s01ldap_loginfilter_username	1
s01ldap_nested_groups	0
s01ldap_override_main_server	
s01ldap_paging_size	500
s01ldap_port	10636
s01ldap_quota_attr	
s01ldap_quota_def	
s01ldap_tls	0
s01ldap_turn_off_cert_check	0
s01ldap_turn_on_pwd_change	0
s01ldap_user_avatar_rule	default
s01ldap_user_display_name_2	
s01ldap_user_filter_mode	1
s01ldap_userfilter_groups	GRUPPE
s01ldap_userfilter_objectclass	
s01ldap_userlist_filter	((memberof=cn=GRUPPE,ou=groups,dc=schule,dc=tld)(memberof=cn=GRUPPE,ou=groups,dc=schule,dc=tld)(memberof=cn=GRUPPE,ou=groups,dc=MEIN-ISERV,dc=de))
s01use_memberof_to_detect_membership	1
types	authentication

From:

<https://wiki.mzclp.de/> - Fortbildungswiki des Medienzentrums Cloppenburg

Permanent link:

<https://wiki.mzclp.de/doku.php?id=anleitung:iservnextcloudldap&rev=1623915495>

Last update: 2021/06/17 09:38

